



NRSM Series
Wire Wound SMD Power Inductor
Size 3012



Dimensions: [mm]



Land Pattern: [mm]




Electrical Properties:

Satura on Satura on

						(Ω)	(Ω)
	±20%	4.80	4.20	10.0	9.30	0.020	0.026
	±20%	4.80	4.10	8.90	7.20	0.024	0.032
	±20%	4.20	3.80	8.00	6.80	0.031	0.040
	±20%	3.60	3.10	6.80	5.80	0.038	0.046
	±20%	3.10	2.70	5.40	4.20	0.046	0.054
	±20%	2.90	2.50	4.10	3.40	0.062	0.074
	±20%	2.35	2.05	3.35	2.80	0.090	0.108
	±20%	1.80	1.50	2.60	2.20	0.144	0.185
	±20%	1.35	1.15	2.50	2.00	0.215	0.255
	±20%	1.25	1.07	1.64	1.32	0.269	0.325
	±20%	1.15	0.97	1.50	1.20	0.340	0.410
	±20%	1.15	0.97	1.45	1.20	0.395	0.474
	±20%	0.60		1.30	1.10	0.610	0.740
	±20%	0.46		1.15	0.96	0.960	1.200

Typical Electrical Characteristics:

Inductance VS. Current Characteristics:



Temperature Rise VS. Current Characteristics:

